

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




8.2

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47G 27/02, 27/04		A1	(11) International Publication Number: WO 98/03104
			(43) International Publication Date: 29 January 1998 (29.01.98)
(21) International Application Number: PCT/CA97/00522		(72) Inventor; and	
(22) International Filing Date: 21 July 1997 (21.07.97)		(75) Inventor/Applicant (for US only): PACIONE, Joseph, Rocco [CA/CA]; 127 Elgin Street, Thornhill, Ontario L3T 1W7 (CA).	
(30) Priority Data: 08/684,004 19 July 1996 (19.07.96) US 08/850,726 2 May 1997 (02.05.97) US		(74) Agents: GRAY, Brian, W. et al.; Blake, Cassels & Graydon, P.O. Box 25, Commerce Court West, Toronto, Ontario M5L 1A9 (CA).	
(60) Parent Applications or Grants		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(63) Related by Continuation US 08/684,004 (CIP) Filed on 19 July 1996 (19.07.96) US 08/850,726 (CIP) Filed on 2 May 1997 (02.05.97)		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant (for all designated States except CA US): TAC-FAST SYSTEMS S.A. [CH/CH]; Route du Bugnon 15, Case postale 106, CH-1752 Villars-sur-Glâne 2 (CH).			
(71) Applicant (for CA only): TAC-FAST SYSTEMS CANADA LIMITED [CA/CA]; Suite 710, 15 Wertheim Court, Richmond Hill, Ontario L4B 3H7 (CA).			

(54) Title: COVERING MODULE AND ANCHOR SHEET



(57) Abstract

A relatively thin flexible anchor sheet (21, 31) for installation under carpets or other decorative coverings and a covering module (19, 21) composed of a pre-attached decorative covering (19) and anchor sheet (21) which can be assembled by overlapping hook and loop attachment to an additional covering module (31, 29) to create a complete floor covering of carpet, tile, stone or other material and without attachment to a floor. Also a temporary hook covering (27) to prevent premature attachment of the hook and loop attachment is disclosed.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MX	Mexico	UG	Uganda
BY	Belarus	IS	Iceland	NE	Niger	US	United States of America
CA	Canada	IT	Italy	NL	Netherlands	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NO	Norway	VN	Viet Nam
CG	Congo	KE	Kenya	NZ	New Zealand	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	PL	Poland	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PT	Portugal		
CM	Cameroon	KR	Republic of Korea	RO	Romania		
CN	China	KZ	Kazakhstan	RU	Russian Federation		
CU	Cuba	LC	Saint Lucia	SD	Sudan		
CZ	Czech Republic	LI	Liechtenstein	SE	Sweden		
DE	Germany	LK	Sri Lanka	SG	Singapore		
DK	Denmark	LR	Liberia				
EE	Estonia						

COVERING MODULE AND ANCHOR SHEET

5

FIELD OF THE INVENTION

This invention concerns a relatively thin flexible anchor sheet for use under carpets or other decorative coverings. In practice, when installed, the anchor sheet acts to tie the decorative covering together as a functional unit and to add mass and stability to such unit, particularly a unit having a flexible decorative covering such as a carpet. An anchor sheet may be substantially covered over one side with hooks for anchoring a decorative covering to it by engagement of complementary loops on the lower side of the covering. The anchor sheet itself may be attached to the underlying substrate, such as a floor or wall, or it may be loose laid on a floor where the sheet and covering together have sufficient mass or are so placed as to prevent movement. It is possible to supply the anchor sheet as a small or large module with pre-attached decorative covering as will be explained later.

BACKGROUND OF THE INVENTION

It is common to attach a decorative flexible covering, such as carpets, to rigid substrates such as floors, made of wood or concrete. It is often desirable, or even required, to fasten carpet to the flooring which it covers and a variety of attachment methods have been developed over the years.

Carpet can be glued directly to the flooring. This is often the approach taken in an institutional setting in which the underlying flooring is concrete and liquid glue is applied across the entire concrete area to be covered. This approach has the advantage that, so long as the adhesive bond provided between the carpet and flooring remains intact, the carpet cannot buckle. Of course, adjustment or replacement of such carpet can be difficult in the sense that previously applied glue might be required to be stripped from the flooring and new glue applied. In addition, such glues often contain volatile organic components that are banned in some places or are required to be ventilated, in other places.

Another approach taken to installing wall-to-wall carpet involves the use of "tackless strips", which are wooden strips having angled tacks driven upwardly therethrough. The strips are secured around the perimeter of the area to be covered, often by nailing them into wooden flooring, and the carpet is stretched over the tacks. This approach has the advantage that the carpet can be restretched to remove a buckle that develops, and the carpet and underpad, not being permanently adhered to the flooring can be removed without being destroyed. However, stretching is a labour intensive art which makes installing wall-to-wall

carpet by this method relatively expensive. This approach also avoids the use of volatile organics, but some difficulties can arise in installing tackless strips to concrete.

More recent approaches involving the use of Velcro-type fasteners have been described in the patent literature: Germany 7,029,524 (August 8, 1970, Velcro France); U.S. 3,574,019 (April 6, 1971, Girard); UK 1,546,901 (May 31, 1979, Allied Chemical Corporation); U.S. 4,822,658 (April 18, 1989, Pacione); U.S. 5,191,692 (March 9, 1993, Pacione); U.S. 5,382,462 (January 17, 1995, Pacione); and U.S. 5,479,755 (January 2, 1996, Pacione). The specifications of all these patent documents are incorporated herein by reference.

U.S. '658 from the same inventor describes a wall-to-wall installation in which hooked strips are secured by pressure sensitive adhesive around a room perimeter and at the carpet seams. A carpet having loops across its backside is cut to fit the room and the loops engage the hooked tape. U.S. '692 describes a method for seaming a carpet such as the one described in U.S. '658. Both of these patent specifications also disclose advantages obtained through the use of a cover for the hooked tape, a primary advantage being that such a cover prevents premature engagement of the hooks and loops to permit proper placement and adjustment of the carpet without the need for disengaging prematurely engaged hooks and loops during installation. This prior approach provides the advantages of installing strips at the perimeter and seams of a carpeted area, particularly that the carpeting can be lifted without being destroyed and the avoidance of the use of compounds containing volatile adhesives.

The "holy grail" of carpet and other decorative covering, would be a system which when laid had such mass and stability as to require little or no attachment to the underlying substrate and which can be installed over existing substrates without the necessity of the removal of existing covering. However for transportation in trucks and to physically fit into a site, such as a room, such a system has to either provide for sufficient flexibility so that it can be rolled or, if rigid, a way of assembling modules so as to form a contiguous mass in situ with sufficient mass and stability to remain in place with minimal detachable attachment or perhaps no attachment, particularly when dealing with different existing floors or flooring surfaces to be covered.

SUMMARY OF THE INVENTION

As previously mentioned, there are advantages to allow the carpet or other decorative covering to be attached to an underlying undersurface at only a few discrete attachment points or even in some cases not attached at all so as to be easily removable. Attachment to the underlying substrate at discrete attachment points provides for minimal damage to the underlying substrate, ease of removal from the substrate and ease of installation. However, a product, method and system is needed to convert these individual attachment points to structurally integrated attachment across the entire undersurface of a carpet or other decorative covering to enable overlaying carpet or other decorative covering to be engineered to maintain atmospheric stability, flatness and horizontal plane stability when

stressed with forces produced by human traffic, rolling vehicles, moving furniture or moisture or temperature changes.

In addition, the system provides that the pieces of carpet or other decorative covering can be integrated together by use of the underlying detachable anchor sheet. Then
5 individual modules can be made consisting of a decorative covering and an anchor sheet attached together in advance of installation at a remote site. Such modules can be easily removed and re-attached as required for repair or replacement or for design reasons. In addition such individual modules can be locked together by overlapping the anchor sheet or decorative covering of adjacent modules so as to give the complete structure sufficient mass
10 and stability to minimize or remove the need for attachment to the substrate.

The present invention in one aspect features an anchor sheet, preferably of plastic, for detachable attachment of a decorative covering such as carpet, ceramic, tile, hardwood, marble or a wall covering to an underlying rigid supporting substrate, such as the surface of flooring or a wall.

15 By providing an anchor sheet preferably in the form of a relatively thin flexible sheet, integrity can be given to covering materials, such as flexible carpets which can be pre-assembled or assembled on site onto the surface of the sheet by the use of a complementary hook on the upper surface of the flexible sheet matching a complementary loop on the undersurface of the carpet or carpet pieces. The sheet can then be installed onto
20 an underlying substrate such as concrete or wood at only a discrete number of points. The anchor sheet enables the installation of decorative covering even onto stone or tile, without significant destruction of the stone or tile floor. It also enables decorative patterns to be pre-assembled at a factory or other location or to be assembled on site by cutting and fitting different colours or pieces of decorative covering together on the anchor sheet to form
25 decorative patterns. Such a system is suitable for either area rugs or wall-to-wall covering and in certain types of wall-to-wall and area rugs, or even tile, it may not be necessary to attach the anchor sheet to the underlying substrate at all. If the carpet is cut to fit the walls or boundaries of a room the anchor sheet may give sufficient integrity to the carpet to allow it to simply sit in the location under constraint of the perimeter walls or other boundaries or if enough furniture,
30 for example, was placed on top. It should be emphasized that the anchor sheet, however, is not structural support in the conventional sense as disclosed for example, in the anchor board of Pacione 5,060,443 since it does not support the floor or wall on which it is placed. It is a vehicle for stabilizing the carpet or other decorative covering which is overlaid and for tying individual pieces of carpet or decorative covering together with each other but not necessarily to
35 the floor. Normally in fact the anchor sheet maintains a certain level of flexibility to enable the anchor sheet to "ride" over imperfections in the floor.

Normally the anchor sheet is relatively thin in relation to the overlying decorative covering, but in some cases, for instance, where there is a thin layer of marble

veneer, then the anchor sheet could be thicker and more rigid than the overlying material and could be made of materials other than plastic such as metal (aluminum or steel) or wood.

Thus, the invention consists of, in one aspect, a detachable anchor sheet for detachable attachment of a decorative covering, such as a carpet, to a rigid supporting
5 substrate, such as a floor, in which the decorative covering has a finished upper surface and an opposite surface substantially covered in loops. The anchor sheet can comprise a relatively thin flexible sheet, preferably of plastic such as a polycarbonate, polyester, polyethylene, or polypropylene, substantially covered with hooks on its upper surface facing the loop surface of the decorative covering and placed intermediate between the decorative covering and the
10 supporting substrate. This flexible anchor sheet or sheets can be, but normally is not, exactly the same size as the combined pieces of overlying sheet goods. Normally overlapping areas of anchor sheet or decorative covering are used to enable tying of the anchor sheets used in a location together. The anchor sheet may be larger than the area under the sheet goods or it can be smaller in cases where it is desired to trim the overlaying carpet to a wall or other
15 boundary. The anchor sheet and decorative covering must in combination have sufficient rigidity to support the decorative covering from shear horizontal force applied to the sheet goods on the floor or other substrate when the combination is laid onto the rigid supporting substrate. In some cases, the anchor sheet will be attached to the substrate at a limited number of discrete points or in some cases along with the covering it may have sufficient rigidity
20 and mass to free float within the boundaries of a room or even on its own.

Thus, in another aspect of this invention it is possible to install decorative flexible anchor sheets to abut each other and to use either the hook covering of the anchor sheet or the overlying decorative covering such as a carpet to tie the abutting anchor sheets together with the use of complementary hook and loop technology. In almost all cases the
25 overlying covering will overlap the joins of the anchor sheets and the anchor sheets will overlap the joins of the covering to tie the anchor sheets and covering together.

It is preferable, but not required in all cases, for the decorative covering to be detachable from the anchor sheet. In the case of smaller modules the decorative covering would normally be pre-installed, and possibly even permanently installed, on the non-
30 decorative anchor sheet leaving an area of anchor sheet or decorative covering exposed for detachable attachment by overlapping with adjoining modules. It is required that this overlapping area provide for detachable attachment and also for a means to prevent attachment during installation to enable the modules to be adjusted for correct alignment during installation. The means for detachable attachment is preferably a hook and loop
35 attachment system, but it could also be an adhesive which provided for multiple opening and closing while maintaining tackiness. In the case where hook and loop is used to join the modules, the covering could be a hand smooth plastic which does not bind to the hook and loop, or one could use a textile or paper hook covering not unlike the hook covering in original patent Pacione '658. For parquet, tile, hardwood, ceramics or other rigid decorative covering, a

flexible tape covering could be used in the overlapping area, which is provided with a pull string which can be pulled from under the pre-assembled covering. This whole process could be duplicated using entirely adhesive or part adhesive and part hook and loop.

Thus, the individual modules of anchor sheet and the individual modules of
5 covering are tied together in a supporting mass which can "free float" on the floor or be connected at only very few discrete points.

In another aspect the invention consists of an anchor sheet or sheets and
pieces of covering in an overlapping staggered relationship to form a contiguous floor covering
having sufficient rigidity, atmospheric stability, horizontal plane stability (shear force stability)
10 and flexibility so that in general use such floor covering may not require attachment to the
underlying floor. Attachment may be required for a small area rug over a slick marble floor or
at a ramp or stairs or where the end use involves heavy traffic.

In another aspect of this invention, decorative modules comprising an anchor
sheet and decorative covering can be pre-assembled offsite by detachably attaching some of
15 the hooks on the upper surface of the anchor sheet to some of the loops on the underside of
the decorative covering so that the decorative covering on the anchor sheet overlaps the
anchor sheet by a predetermined amount. These pre-assembled decorative modules can then
be shipped to the site and individually placed on the underlying substrate in an abutting fashion
to permit interlocking between the loops on the underside of the decorative covering of one unit
20 and the hooks on the upper surface of the anchor sheet of an adjacent decorative module.
Each decorative module added to the growing modular surface covering can be guided into its
proper position by placing thin, rigid pieces of plastic over the exposed hooks of the anchor
sheet of an established decorative module. After properly aligning the decorative module to be
added to the established module, the thin, rigid plastic pieces are slid out and away from the
25 two modules, parallel to the horizontal plane, thereby allowing the abutting module to become
engaged through a hook and loop system. The thin, rigid pieces of plastic can also be used to
detach individual modules of the modular surface covering. The thin, rigid plastic is inserted
between the mechanically bonded portions of the hook and loop fastener of abutting modules,
parallel to the horizontal plane, thereby breaking the mechanical bond and maintaining the
30 hooks and loops out of contact with one another to enable the units to be dislodged and
removed from the modular surface covering.

In another aspect, the invention consists of a covering module for
transportation to a surface to be covered and for attachment to additional modules to form a
finished decorative surface comprising at least one decorative covering having an upper
35 decorative surface and an opposite lower surface, a non-decorative anchor sheet having an
upper surface, the decorative covering attached across a substantial portion of its lower surface
to the non-decorative anchor sheet and the anchor sheet dimensioned so that, after attachment
of the decorative covering to the anchor sheet, there is provided an overlap area of upper
surface of anchor sheet exposed along at least one edge of the module which overlap area is

- 6 -

provided with means for detachable attachment of such module to an adjoining module by attachment to an overlapping area of the lower surface of a decorative covering attached to an adjoining module.

- Covering modules of an unlimited variety of shapes and sizes can be
- 5 constructed and decorative patterns may be assembled on site by combining different colours or patterns of the same type of decorative covering, such as alternating between units of red and blue carpet or by combining different types of decorative covering such as carpet and hardwood in a hotel, restaurant or ballroom setting or carpet, hardwood, ceramic or stone in a home setting. In general use, such contiguous covering could have sufficient rigidity and mass
- 10 so as not to require attachment to the underlying surface. In some cases, attachment of the anchor sheet at discrete points may be required as for example, when the surface to be covered is a wall.

BRIEF DESCRIPTION OF THE DRAWINGS

- Embodiments of the invention will now be described, reference being had to
- 15 the accompanying drawings, wherein:

Figure 1 shows anchor sheets of a first embodiment of the system of the invention laid side by side on a floor with a temporary hook covering bridging the abutting joins to tie the sheets together.

- Figure 2 shows a section of anchor sheet laid onto a floor with the sheet
- 20 covered with separate detachable hook cover pieces A-A at a boundary.

Figure 3 shows a section along the lines 3-3 in Figure 1 with a connecting hook cover piece.

Figure 4 shows carpeting laid onto the anchor sheeting of Figure 1.

Figure 5 shows a section along the lines 5-5 of Figure 4.

- 25 Figure 6 shows pre-assembled carpeting and anchor sheet together being laid in abutting overlapping relationship onto a floor.

Figure 7 shows a section along the lines 7-7 in Figure 6.

Figure 8 shows an alternative embodiment with a separate carpet piece bridging abutting anchor sheets.

- 30 Figure 9 is a section along the lines 9-9 of Figure 8.

Figure 10 shows another arrangement of anchor sheet and carpet with a decorative pattern.

Figure 11 shows an area rug installed on an anchor sheet having a lip.

Figure 12 is a section along the lines 11-11 of Figure 12.

- 35 Figure 13 is yet another embodiment of anchor sheet and overlying decorative covering pieces which has not been created from modular units.

Figure 13a is yet another embodiment of anchor sheet and overlying decorative covering pieces pre-assembled as individual modular units and laid in an abutting and overlapping fashion.

Figure 14 shows an anchor sheet having an upper surface substantially covered with hooks and an optional cushion on the underside of the anchor sheet.

Figure 15 shows a decorative covering module having a decorative finished upper surface and an underside substantially covered with loops.

Figure 16 shows one covering module of a modular surface covering having a decorative covering detachably precision attached in an overlapping manner to an anchor sheet by means of hook and loop technology.

Figure 17 shows a section along lines 17-17 of Figure 16.

Figure 18 shows two pre-assembled covering modules being laid in an abutting overlapping relationship onto an underlying substrate.

Figure 18a shows three pre-assembled covering modules laid in an abutting overlapping relationship on an underlying substrate and a fourth covering module being installed.

Figure 19 shows a portion of a finished modular surface covering.

Figure 20 shows a section of two covering modules attached together.

Figure 21 shows another arrangement of the modular surface covering composed of covering modules of a rectangular size and shape.

Figure 22 shows another arrangement of the modular surface covering representing a decorative pattern with artificial grout separating carpet tiles.

Figure 23 shows a decorative pattern separator for use in the arrangement of Figure 22.

Figure 24 shows one way in which the covering modules assembled as shown in Figure 22 may be delivered on site.

Figure 25 shows another arrangement of covering modules as an alternative to the arrangement shown in Figure 22.

DESCRIPTION OF PREFERRED EMBODIMENTS

Turning to the drawings, a first embodiment anchor sheet 1 is illustrated in Figure 1 having abutting anchor sheets 3 and 5. Each anchor sheet is covered with plastic or filament hooks 7 which can be better seen in Figures 2 and 3 similar to hooks currently used on conventional hook and loop fastening systems. Covering pieces 9, preferably of cloth, cover the hooks 7. The covering could also be a film. The covering can be better seen in Figures 2 and 3. In order to keep the hooks 7 clean and to prevent premature attachment of a to-be-installed overlying covering, this form of anchor sheet is completely covered with a covering. Preferably there is a separate covering strip 11 of a width A, as shown in Figure 2, which establishes a pre-cut slit 12 in the covering of a width A along the border of each anchor sheet.

While the anchor sheet can be provided in rolls as described later, in the embodiment of Figure 1 it is simply a sheet, for instance, a rectangle of four feet by eight feet. It can be laid on the floor, in the case of a wall-to-wall installation, in continuous abutting relationship to other anchor sheets to cover the entire surface of the floor or other rigid substrate. As it is covered with coverings 9 and strips 11, it is possible to lay and install carpet on it without premature attachment of the hooks 7 and complementary loops. The carpet constructed, for instance, as disclosed in U.S. Patent No. 4,822,658 (Pacione) can be installed onto this anchor sheet.

However when working on the anchor sheet with carpet, it may be preferable if the anchor sheets are at least anchored to each other and possibly pre-attached at discrete locations to the floor. Anchor sheets can be attached to each other by the removal of precut hook covering strips 11 on either piece of abutting anchor sheets for instance 1 and 3 and replacement of such hook covering with a bridging piece of hook covering for instance 13 which covers the join between abutting anchor sheets and attaches them to each other. Strip 13 can cover the join between a number of anchor sheets. For instance in Figure 1, it is also covering the abutting join between anchor sheet 8 and 10 as well.

Anchor sheets can also be attached to the floor at discrete locations such as at point 14. The anchor sheet can be glued down, attached by hook tape affixed to the floor and attachable to complementary loops on the back of the anchor sheet, or attached by double-sided adhesive tape, but in most cases the simplest form of attachment of the anchor sheet to the rigid substrate, particularly if the substrate is, for example, a wooden floor, is to attach the anchor sheet at discrete points by the use of nails or tacks. Such discrete points are shown at 14 in Figure 1 and in this case it is advisable to have perforations, slits or holes in hook cover sheet 9 so as to enable the anchor sheets such as 1, 3, 5 etc. to be nailed to the floor through the hook cover sheets 9 without the head of such nail or tack attaching the hook cover sheet 9 permanently to the anchor sheet 1, 3, 5 etc. so that such sheet can be removed after the overlying carpet has been cut and fit in place for attachment of the overlying carpet to the anchor sheet. In addition, depending on the thickness or brittleness of the anchor sheets, it may be advisable to have pre-drilled holes in the anchor sheets.

Depending upon the form of attachment, if any, of the anchor sheet to the floor, it may not be necessary to attach the anchor sheets to each other by the use of bridging hook cover 13 during installation of the carpet.

It may also be possible, depending upon where the underlying carpet joins occur, to leave bridging tape 13 attached to the anchor sheets since there will be normally sufficient attachment of the carpet to the anchor sheet in a large area underneath hook cover 9. It is not necessary to attach the anchor sheets to the underlying floor substrate in every situation. The overlying carpet (not shown in Figures 1, 2 or 3) will provide additional mass and rigidity to the anchor sheets which will be firmly attached to each other by such overlying carpet. In this case, depending upon the mass of the carpet and the rigidity of the anchor sheets, the combination may be firmly enough attached in place by the surrounding boundaries of the walls

or other perimeter of the room or area in which the anchor sheet and carpet have been installed.

In some cases, given a large enough carpet area, and depending upon the underlying floor structure, it may not be necessary even to attach area rugs to the underlying floor since they may have sufficient mass to remain in place without substantial movement on their own. It will also depend, for instance, in the case of both area rugs and wall to wall carpet on whether or not furniture or other heavy objects are installed on the combination carpet and anchor sheet.

In some cases, the abutting anchor sheets as shown in Figure 1, will be installed under carpets of a wider width than the anchor sheet so that the carpet overlaps the anchor sheet as shown in Figure 4. Loops 17 on the back of the carpet are engageable with hooks 7 when the cover 9 has been removed. For installation, carpet 15 is rolled out onto the anchor sheets which are entirely covered by a hook covering 9. The carpet can now be cut and fit and adjusted in place and abutted against another carpet roll before any attachment to the underlying anchor sheet 1 is made. In Figure 5 is shown a cross-section of the anchor sheet and carpet prior to removal of the hook covering 9 or 13. Thus carpet 15 overlaps join 17 between abutting anchor sheets 1 and 3. Anchor sheets 1 and 3 are possibly attached to the floors as previously described and they are also attached to each other by hook covering 13 bridging join 17. Once covering 9 is removed, at least part of anchor sheet 1 and at least part of anchor sheet 3, are now both attached to carpet 15 so that carpet 15 now also bridges the join 17 between anchor sheets 1 and 3 and ties such anchor sheets together. It is possible, and even in some situations preferable, to also remove bridging hook cover 13. However, it is not always necessary to do this. Once at least hook covering 9 is removed, the carpet and anchor sheet whether or not attached to the underlying substrate form a contiguous rigid floor covering of relatively great strength, mass and rigidity which does not buckle under ordinary use even if there has been no attachment directly to the floor.

The anchor sheet itself is preferably made of thin polycarbonate, polyethylene, polypropylene or polyester of preferably from 10/1000 to 20/1000 thickness. The thickness may vary depending upon the covering material and the stability requirements for the carpet. It is also possible for the anchor sheet to be made of thin sheet metal, carbon fibres or some form of polymer. The anchor sheet can include a foam layer which provides resiliency. Hooks can be attached to the sheet by any conventional means but extrusion or co-extrusion are the preferred methods.

Thus the anchor sheets and carpet together are, in many situations, thin enough and flexible enough to be rolled as a single unit. This enables the carpet, in some embodiments, to be pre-installed onto the anchor sheet in which case it can be more easily installed as shown in Figure 6.

In this case, carpet 19 installed on anchor sheet 21 (as seen in Figure 7) is rolled onto the floor and cut to fit adjoining walls 23 and 24.

Carpet piece 19 and anchor sheet 21 is delivered to the site in the same form as carpet piece 29 and anchor 31 but in the case of the part which abuts wall 23, the extra carpet may be trimmed off or left as it is not a necessity that the anchor sheet abut the wall.

It has come pre-installed (as can better be seen in Figure 7) onto anchor sheet 21 which is, in this case, bigger than carpet piece 19 so as to leave exposed an area of hooks 25 covered with a hook covering 27. Most carpet rolled in this way will be installed on an anchor sheet at a factory with an overlap as shown for carpet piece 29 so that the carpet overlaps on one side of the anchor sheet 31 and on another side the anchor sheet 31 itself extends beyond carpet piece 29. Carpet and anchor sheet combination 29 and 31 are then unrolled to abut carpet piece 19 and can be cut and fit in place after which hook covering 27 can be removed by pulling the hook covering up thereby rolling back carpet piece 29 or in some cases by pulling the covering 27 up and through join 33. Carpet piece 29 is now firmly attached to both anchor sheet 21 and 31 and, as it bridges the join 35 between the two of them attaches the two anchor sheets together. It is now possible to repeat this process by laying an additional similar carpet roll over hook covering 37 and remove such hook covering to attach the next adjoining carpet piece to anchor sheet 31 and to repeat this process again and again until the room is covered in carpet and anchor sheet in a continuing piece.

If it is necessary to attach the anchor sheets to the floor, it can be done in the area exposed where the anchor sheet hooks and hook covering are not covered by the pre-installed carpet roll such as at 39 or 41. In this case the hook covering 27 or 37 can have perforations, slits or holes so that a nail or tack attached through the hook covering will not attach the hook covering to the underlying anchor sheet so that it can be removed as previously described. Attachment of the anchor sheet to the floor at for instance strips 39 and 41 should be sufficient attachment in many, if not most, instances, especially when combined with the fact that the decorative carpet covering also ties the anchor sheets together as a single unit.

There is an advantage in some situations to install the carpet over an anchor sheet in a factory. The factory can cut and fit a number of different carpet pieces onto the anchor sheet, both for decorative purposes and for transportation of the carpet pieces together as one piece. Thus as shown in Figure 6 it is possible to have an insert, for instance 43, repeated with a decoration or pattern at intervals on the carpet roll and with smaller geometrical inserts 45. Typically these inserts would be of a different colour or different design or pattern to create a pleasing carpet pattern.

Figure 8 shows an additional form of carpet installation. In this case the carpet and anchor sheet will be delivered from the factory attached but the carpet, for instance 47, is narrower than the anchor sheet 48 to leave an exposed area of anchor sheet hook 49 and hook covering 50 of approximately width C as shown in Figure 9 on both longitudinal edges. In this case, the carpet is unrolled and, if desired, attached to the underlying floor. Another similar anchor sheet 51, having installed thereon carpet 52 is unrolled and abutted to anchor sheet 48 (seen in Figure 9). Anchor sheet 53 is also unrolled and abutted to anchor sheet 51. Anchor

5 sheets can be attached to the floor by, for instance, nailing through strip areas 55, 57, 59 and 61 since at this stage of the installation, those areas do not contain a carpet covering. Bridging carpet strip 63 can be fit to the area not covered by carpet 55 and 57 (the area labelled D in Figure 9). After fitting, underlying hook coverings 50 and 54 can be removed so that carpet piece 63 can be installed on the anchor sheet to bridge and firmly attach anchor sheet 48 to anchor sheet 51. A similar process can then be followed for anchor sheet 53.

10 Normally this form of installation would be used where it is desired to have carpet strip 63 of a different colour or pattern than carpet pieces 47 and 52 so as to provide a decorative border around individual carpet areas 47 and 52 51. In this case, it is likely that the pattern or border will also be contained along edges 65 and this can be easily accommodated by installing carpet piece 47 of a size smaller than the anchor sheet 48 to create strip 65 of any desired thickness. This form of installation may also allow for room variations since the carpet trim at the border is installed and trimmed last.

15 Again it is possible for anchor sheets 48 and 51 to be attached to the floor either by tacking or nailing or also by a complementary hook and loop attachment system, or (although it is usually not preferable) by gluing or pressure sensitive double-sided tape.

20 In Figure 10 is shown another form of pattern 67 containing a central medallion 69 and corner pieces 71 installed on an anchor sheet 73. In this case the anchor sheets and carpet pieces simply abut and are attached to the floor by small pieces of hook tape 75 which will normally have hook covering (not shown), hooks on an upper surface and a pressure sensitive adhesive 77 on a lower surface for attachment to the floor. The pressure sensitive adhesive will normally have a peelable dry strippable covering.

25 In this case the carpet 67 and anchor sheet 73 can be attached by individual pieces 75 at the corners which can overlap with the adjoining carpet pieces. Strips could also be used along joins between for instance carpet pieces 67 and 79, but if a number of pieces is to be used, normally an overlapping modular system such as shown in Figure 19 would be used, since this assists in holding seams in place and assists with gauge differential problems that might exist between different carpets which could cause seam abuse. If a modular system is used attachment points to the underlying floor may not be required.

30 This same pattern could be used as described later, without attachment to the floor by overlapping piece 79 for instance onto adjoining anchor board 73. In this case, of course, piece 67 must be made shorter.

35 One advantage of the anchor sheet system is that carpet inserts 69 and 71 can be removed, replaced, or exchanged if different colours or patterns are desired and similarly as shown in Figure 6 inserts 43 and pieces 45 can also be removed and changed. Any pattern can be inserted, and if standard sizes are used, the patterns can be interchangeable so as to convert the carpet piece from for instance a boy's pattern to a girl's pattern or from a living room pattern to a bedroom or bathroom pattern.

Another prime advantage is that the anchor sheet need only be attached at a discrete corner area such as with pad 75 shown in Figure 10 but, nevertheless, carpet pieces 67, 69, 71 and 72, for instance, are all attached across their entire undersurface on the anchor sheet 73 so that a pattern can be inserted or replaced at any point.

5 As shown in Figure 12, an area rug can also be created in which carpet piece 81 is installed over anchor sheet 83 as best seen in Figure 12. Anchor sheet 83 has upturned or curled lip 85 which covers the exposed edges 87 of the carpet.

10 An anchor sheet for such area carpet can be attached by nails or by hook and loop technology (if the underside of the anchor sheet is covered in loops and is then installed with corresponding hooked tape). In most cases it would be sufficient to simply attach the anchor sheet at discrete points to the underlying floor by a small piece of loop tape attached by pressure sensitive adhesive to the underside of the anchor sheet 83 matched to a corresponding small piece of hook tape attached by pressure sensitive adhesive to the floor. In some cases the area carpet may have sufficient mass and stability not to have to be attached to
15 the underlying floor at all. The need for attachment is reduced if, for instance, anchor sheet 83 has a non-slip surface on its underside. With the anchor sheet disclosed it is possible to attach area rugs to granite, marble or stone, floors to which it has been difficult to apply area rugs in the past. In addition, carpet 81 can, like carpets 67 and 19, have inserted patterns and those patterns can be quite elaborate allowing, for the first time, a relatively cheap patterned rug
20 which can mimic even, for instance, oriental carpets, in which a large number of carpet pieces are installed over a unitary anchor sheet 83. It is even possible to create a crazy quilt or a do-it-yourself carpet using carpet pieces installed over a pre-formed anchor sheet 83.

As shown in Figure 13, anchor sheets 89 can be made in smaller modules. Decorative covering such as carpet pieces 91, can be, for instance, carpet tiles, and if they are
25 laid in overlapping relationship as shown in Figure 13, a contiguous mass can be formed by anchor sheets 89 and carpet pieces 91, which would be sufficient to provide for stable installation without attachment to a floor. This would particularly be the case if piece 91 is not carpet but parquet or another rigid decorative covering. If however it is desired to attach the anchor sheets 89 to the floor, that can be easily done by tacking or nailing, or using
30 conventional hook and loop technology. In this case again it would be preferable to have slits, perforations or holes 93 in the tape covering 95 (if tape covering is used) so that the anchor sheet can be attached to the floor before removal of any hook covering, but without the attachment of the hook covering to the floor.

In Figure 13a is shown a similar arrangement to Figure 13, but in which the
35 pattern is built in a modular way so that, for instance, units of a covering 91 and an anchor sheet 89 can be created before assembling the entire surface covering. A form of such units, which we call covering modules, is described below.

As shown in Figures 14 and 15, in an additional form of installation, covering modules comprising an anchor sheet 96 having an upper surface covered substantially with

hooks 97, with an optional cushion on its lower surface 98 and a decorative covering 99 for placement over the anchor sheet having a decorative finished upper surface 100 and a lower surface substantially covered with loops 101 are detachably preattached offsite in an overlapping manner along surface AA as shown in Figure 17 such that an area of hooks are left exposed BB while some of the loops on the underside of the decorative covering are also left exposed CC. Covering pieces (not shown), preferably of cloth can cover the hooks 97, but are not necessary where temporary coverings 106 as seen in Figures 18 and 18a are used. It might be advisable to use covering pieces to prevent dirt from covering the hooked surface before assembly.

These pre-assembled covering modules are then shipped to the site and as shown in Figures 18 and 18a, placed on the underlying substrate individually, in an abutting fashion, in order to engage the exposed loops 101 on the underside of the decorative covering of one covering module and the exposed hooks 97 on the upper surface of the anchor sheet of an adjacent covering module. As shown in Figure 18, each covering module 105 added to the growing modular surface covering is guided into its proper position by laying thin, rigid pieces of plastic 106, over the exposed hooks of the anchor sheet of the established covering module 107. The rigid pieces of plastic permit placement and adjustment of the unit without premature engagement of hooks and loops during installation. After properly aligning the loops on the underside of the decorative covering of one covering module with the hooks on the upper surface of the anchor sheet of the abutting covering module, the thin, rigid pieces of plastic are slid out parallel to the horizontal plane and away from the two units thereby enabling the abutting units to become engaged through hook and loop technology. Any hook covering pieces (not shown) of the recently added covering module are then removed in preparation for the addition of a subsequent covering module. This step by step process of attaching covering units to adjacent covering units mechanically bonded through hook and loop technology is repeated to create a contiguous surface covering as shown in Figure 19. Figure 20 shows a section of two covering modules attached together.

A disadvantage of using covering modules is the difficulty of aligning them over a great distance. The anchor sheet should preferably be precisely located in relation to the neighbouring anchor sheet and the decorative covering should preferably be precisely located in relation to the decorative covering of a neighbouring covering module. If the length AA, BB or CC (as shown in Figure 17) is off by even a small amount, this amount multiplied over many modules will result in a misalignment of the surface covering. Thus unless the anchor sheet and the decorative covering are precisely aligned on the covering module, it will not be possible in practice to easily install an overlapping system, such as disclosed here. In practice, it is necessary to have these modules preattached in a precise relationship as shown in Figure 17, preferably by preassembly at a factory using a machine for accurate alignment. It is also possible but slow to use a pattern or form at the point of installation for maintaining a constant alignment of the decorative covering with the anchor sheet.

One advantage of this form of installation is that an unlimited variety of patterns can be created. Decorative coverings or the entire covering module can be removed, replaced or exchanged if different colour or pattern combinations are desired. Any pattern can be inserted and if standard sizes are used, patterns can be interchangeable. For example, units of
5 different coloured carpet can be installed to create a unique carpet design or a combination of different types of covering modules, such as carpet and hardwood or ceramic and marble can be combined and subsequently replaced or exchanged to form yet other unique arrangements.

To facilitate this process, the thin, rigid pieces of plastic discussed above can also be used to detach individual units of the modular surface covering. The thin, rigid pieces
10 of plastic are inserted between the mechanically bonded portions of the hook and loop fastener of abutting units, parallel to the horizontal plane, thereby breaking the mechanical bond and maintaining the hooks and loops out of contact with one another to enable the units to be dislodged and removed from the modular surface covering.

Another advantage is that in most cases, the mass of the decorative covering
15 and the rigidity of the anchor sheet when attached together will enable the modular surface covering resulting from the hook and loop attachment of abutting covering modules, to abutting anchor sheets to be held firmly in place without the need for attachment to the underlying substrate. However, if it is necessary to attach selected covering modules to the substrate, as for example, with a wall covering, that can be done by tacking, nailing, gluing or by use of hook
20 and loop technology. The exposed portion of the anchor sheet of a covering module yet to be bonded through hook and loop technology to a subsequently added abutting module can be used for tacking to the underlying substrate. Such exposed portion is then covered by a decorative covering of an abutting covering module. Such discrete tacking points could be as shown at 108 in Figures 16, 18, 19 and 21. Attachment of the anchor to the substrate at points
25 108 or even fewer points should be sufficient attachment in many, if not most, instances. Depending on the thickness or brittleness of the anchor sheets, it may be advisable to have predrilled holes in the anchor sheets. In this case again it would be preferable to have slits, perforations or holes (not shown) in the tape covering (not shown) so that the anchor sheet can be attached to the floor before removal of any hook covering, but without the attachment of the
30 hook covering to the floor.

Shown in Figures 22, 23, and 24 is an additional carpet or ceramic tile pattern using covering modules 110 such as shown in Figure 24. Such covering modules consist of an anchor sheet 112 and a tile or decorative covering 114 which can be of ceramic or carpet or any other suitable material. Normally the tile or decorative covering 114 and anchor sheet 112
35 are pre-attached at a factory in a precisely pre-determined relationship as shown. If the tile or decorative covering contains loops across its undersurface and the anchor sheet hooks across its top surface, then detachment and reattachment are possible if required on site. A permanent adhesive can be used for a permanent bond between tile 114 and anchor sheet

112 or a temporary adhesive having the properties of hook and loop (i.e. can be attached and reattached and good horizontal strength) can be used.

Assuming hook and loop is used, then the anchor sheet 112 will be covered in hooks similar to hooks 97 in Figures 14 and 18 and, the underside of the tile will be covered in loops similar to loops 101 in Figures 15 and 17. Tile or decorative covering such as 116 in Figure 22 overlaps and binds to anchor sheets 112, 118, 120 and 122 and helps to tie those anchor sheets together. If the tile is carpet tile, then tiles such as 114, 116 and others including centre tile 124 can be formed by dye cutting of a larger carpet piece. In this case "grout" shaped spacing pieces 126 as shown in Figure 23 are formed. If other carpets of contrasting colours are also cut, these pieces can be used with other similarly shaped patterns cut from such carpets. This piece 126, if it came from the carpet used to make tile 114 or 124 would go off for use in another pattern and a new piece (not shown) of the same shape as piece 126 would be included (from a dye cutting of a carpet of a contrasting colour).

By using such decorative pattern separators, such as 126, the places where similar colours meet can be minimized. By providing a contrasting colour for piece 126, the eye is drawn to the pattern rather than any imperfections where straight lines of similar but not identical dye lots meet. Thus in the pattern of Figures 22 or 25, similar colours meet only at, for instance, 125 in Figure 23 or 119 in Figure 25. It is possible to provide a third or even more colours to eliminate places where the same colours meet, which could provide difficulty for subsequent matching. Shown in Figure 25 is another arrangement in which, for instance, tile 128 is placed on anchor sheet 134. The pattern is similar but the tile or decorative covering is in a different orientation to anchor sheet 134. In this case tile 128 for instance overlaps anchor sheet 130 and 134, but anchor sheet 134 and 136 are attached by medallion 132 and also by an insert or "grout" 126 as shown in Figure 23, which has not yet been installed in the arrangement of Figure 25.

In the case where tiles such as 114 or 128 are ceramic tiles, it is possible to size them in relation to the anchor sheet so that the space between, for instance, tiles 114, 116 and medallion 124 is less than shown in Figure 22, and then a resilient grout, such as rubber caulking, could be friction fit into the space between the tiles to simulate real grout or the rubber caulking could be provided as an elastic band of a size to fit around tile 114 or medallion 124. Such elastic band could even be preinstalled onto the tile before the covering modules such as 110 are assembled. Additionally even real grout could be used directly into the space between the tiles.

The anchor sheet of this invention in its various embodiments allows for increased versatility in the installation of decorative coverings or carpets that have been created with loops such as the hook and loop system disclosed in Pacione U.S. 4,822,658. Using the covering modules, in which the decorative covering and anchor sheet are pre-attached, it is possible to reduce the attachment area to an exposed overlapping area and to use an adhesive which can be pulled apart and re-attached or hook and loop in such exposed area. With the

- 16 -

anchor sheet, carpets and other decorative covering can be installed easily on almost any surface without destroying the surface and they can be, in many instances, pre-assembled at a factory and the carpets or other decorative covering only need to be attached to the underlying surface, if at all, at a few discrete places. This removes the necessity of having to remove

5 underlying substrate such as carpet or hardwood and having to strip adhesives such as glue from the surface. Large quantities of decorative covering such as carpet no longer have to be disposed of as they are simply covered by a new decorative covering. Further, with this invention, it is now possible to maintain a valuable flooring, such as marble, intact for later use, but to temporarily cover such flooring with carpet or tile.

10 While certain embodiments of the invention have been disclosed, it is intended to cover all variations and combinations of the invention as claimed in the attached claims.

CLAIMS

1. A covering module for transportation to a surface to be covered and for attachment to additional modules to form a finished decorative surface comprising:
at least one decorative covering having an upper decorative surface and an opposite
5 lower surface, a non-decorative anchor sheet having an upper surface, the decorative covering attached across a substantial portion of its lower surface to the non-decorative anchor sheet and the anchor sheet dimensioned so that, after attachment of the decorative covering to the anchor sheet, there is provided an overlap area of upper surface of anchor sheet exposed
10 attachment of such module to an adjoining module by attachment to an overlapping exposed area of the lower surface of a decorative covering attached to an adjoining module.
2. A covering module for transportation to a surface to be covered and for attachment to additional modules to form a finished decorative surface comprising:
at least one decorative covering having an upper decorative surface and an opposite
15 lower surface, a non-decorative anchor sheet having an upper surface, the decorative covering attached across a substantial portion of its lower surface to the non-decorative anchor sheet and the anchor sheet dimensioned so that, after attachment of the decorative covering to the anchor sheet, there is provided an overlap area of lower surface of the decorative covering
20 detachable attachment of such module to an adjoining module by attachment to an overlap area of the upper surface of an anchor sheet attached to an adjoining module.
3. A covering module as claimed in claims 1 or 2 in which the means for detachable attachment in the overlap areas of anchor sheet and decorative covering are one portion of a complementary hook and loop attachment system substantially covering the overlap area of
25 the anchor sheet to be matched with the complementary second portion of such hook and loop system on the overlap area of an adjoining decorative covering.
4. A covering module as claimed in claim 3 in which there is provided on site a temporary covering for the overlap area of attachment to prevent attachment of such module to an adjoining module until the module and adjoining module are in the desired position relative to
30 each other.
5. The covering module of claim 4 in which the temporary covering is a thin smooth sheet of at least substantially the size of the overlapping area, which cannot bind to either complementary hook or loop portions.

6. A covering module as claimed in claim 5 in which the temporary covering is sufficiently rigid and thin so that it can be pushed between the complementary hook and loop bonds of an attached decorative covering and anchor sheet to break such bonds in the area of such covering to enable readjustment of a decorative covering in relation to an anchor sheet or one module in relation to another.
7. A covering module as claimed in claim 1 or 2 in which the decorative covering and non-decorative anchor sheet are precisely dimensioned and attached off site in alignment to provide for a pre-determined overlap area of anchor sheet and decorative covering so that when the anchor sheet of a first module is placed in position next to an adjacent second module the decorative covering of the first module overlaps the second module by a predetermined amount and in a predetermined relation to the decorative covering of the second module.
8. A covering module as claimed in claim 7 in which the decorative covering and the non-decorative anchor sheet of each module are attached by means of a complementary hook and loop attachment system covering the lower surface of the decorative covering and the upper surface of the anchor sheet.
9. The covering module of claim 1 in which there is provided an additional overlap area of exposed anchor sheet along a second edge of the carpet module.
10. The covering module of claim 2 in which there is provided an additional overlap area of exposed decorative covering along a second edge of the carpet module.
11. The covering module of claim 3 in which the lower surface of the anchor sheet is provided with a resilient undercushion.
12. The covering module of claim 3 which is laid onto a floor and is attached to adjacent like modules so as to form a covering of sufficient mass and rigidity to remain in place on a floor without buckling or movement when subject to normal traffic and without attachment to the floor.
13. The covering module of claim 12 in which the lower surface of the anchor sheet is provided with a non-slip covering.
14. A covering module for transportation to a surface to be covered and for attachment to additional modules to form a finished decorative surface comprising:
- a decorative covering having an upper decorative surface and an opposite lower surface, a non-decorative anchor sheet having an upper surface, the decorative covering attached to the non-decorative anchor sheet and the anchor sheet dimensioned so that, after attachment of the decorative covering to the anchor sheet, there are provided first overlap areas of upper surface

of anchor sheet exposed along at least two adjacent edges of the module, and second overlap areas of lower surface of decorative covering exposed along at least two edges opposite the first overlap areas, which overlap areas are provided with means for detachable attachment of such module to an adjoining module by attachment to an overlap area of an adjoining module

5 by means of a complementary hook and look attachment system.

15. The covering module of claim 14 in which is provided with a temporary hook covering for the overlap area.

16. The covering module of claim 15 in which the anchor sheet is covered on its underside with a resilient cushion layer.

10 17. An anchor sheet for detachable attachment of decorative coverings to a rigid supporting substrate, the decorative coverings having a finished surface and an opposite surface substantially covered in loops, comprising:

a thin flexible sheet substantially covered with hooks on a surface facing the looped surface of the flexible decorative covering and placed intermediate between the

15 covering and the supporting substrate, the sheet substantially covering the supporting substrate under the covering and having, in combination with the covering, sufficient rigidity and mass to support the covering from buckling of the covering across the entire surface of the covering when the covering is attached to the anchor sheet and laid onto the substrate.

20 18. An anchor sheet for attachment of decorative sheet covering having a reverse face substantially covered in loops, comprising:

a thin flexible anchor sheet having an upper face substantially covered with hooks, located intermediate to the covering and the supporting substrate with the hooks in releasable engagement with the loops of the sheet covering, one or more sheets

25 being installed side-by-side substantially to cover the supporting substrate under the covering, wherein the sheet and covering together have sufficient rigidity to support the system against buckling forces on the covering when laid on the substrate.

19. The anchor sheet claimed in claim 17 in which the sheet is detachably attached to a supporting substrate at a limited number of discrete points.

30 20. The anchor sheet claimed in claim 18 in which the sheet is free floating on the floor.

21. The anchor sheet of claim 20 in which the sheet has sufficient mass and rigidity to remain in place without attachment to the supporting substrate.

- 20 -

22. The anchor sheet of claim 17 in which there is a resilient layer covering the anchor sheet on the side opposite the hook surface.
23. A covering module comprising:
- (a) a relatively thin flexible anchor sheet having an upper surface of the anchor sheet covered substantially with hooks
 - (b) a decorative covering for placement over the anchor sheet having a decorative finished upper surface and a lower surface substantially covered with loops and in which the lower surface of the decorative covering is detachably attached in a predetermined relationship to the upper surface of the anchor sheet by means of at least some of the hooks and loops so that the decorative covering on the anchor sheet overlaps the anchor sheet by a predetermined amount to permit interlocking between the decorative covering and an adjacent anchor sheet
 - (c) removable hook covering on the upper surface of the anchor sheet to prevent the premature attachment of the hooks on the upper surface of that anchor sheet to the loops on the lower surface of an overlaying decorative covering.
24. The covering of claim 23 in which the lower surface of the flexible anchor sheet is covered by a cushioned underpad.
25. The covering of claim 23 in which the hook covering is placed over the hooks during installation.
26. The covering of claim 25 in which the hook covering is a thin, rigid piece of plastic of predetermined length and width to match the area of overlap of anchor sheet and adjacent decorative covering.
27. A method of installing a covering comprising the steps of:
- (a) selecting an anchor sheet covered on one side with hooks
 - (b) installing decorative covering substantially covered on one side with complementary loops onto the anchor sheet in a predetermined relationship to the anchor sheet to create a unit with an overlapping exposed area of anchor sheet and decorative covering
 - (c) repeating step (b) as required to create a number of units of decorative covering and anchor sheet having exposed areas of anchor sheet and decorative covering
 - (d) temporarily covering at least a portion of exposed anchor sheet
 - (e) overlapping an exposed area of decorative covering from a different unit created during step (c) onto the exposed area of anchor sheet temporarily so covered

(f) removing the temporary covering.

28. The method of claim 27 in which step (b) requires that the predetermined relationship established leaves exposed areas along at least two edges of the unit created in step (b).

1/17






FIG. 1

2/17

FIG. 2FIG. 3

3/17




FIG. 4




FIG. 5

4/17




FIG. 6

5/17






FIG. 7

6/17



7/17




FIG. 10




FIG. 11

8/17




FIG. 12




FIG. 13

9/17




FIG. 13a

10/17




FIG. 14




FIG. 15




FIG. 16

11/17




FIG. 17




FIG. 19

12/17




FIG. 18

13/17




FIG. 18a

14/17




FIG. 20

15/17




FIG. 21

16/17




FIG. 22




FIG. 23




FIG. 24

17/17




FIG. 25

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CA 97/00522

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A47G27/02 A47G27/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A47G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 649 069 A (TONE) 10 March 1987	1-3,7, 9-14,16
Y	see figures 3,4	4,5
X	GB 1 546 901 A (ALLIED CHEMICAL CORPORATION) 31 May 1979 cited in the application see claim 12	17-22
X	US 5 382 462 A (PACIONE) 17 January 1995 cited in the application see column 2, line 8	18,20, 21,23,24
X	US 5 191 692 A (PACIONE) 9 March 1993 cited in the application	23,25
Y	see column 4, line 48 - line 53; claims 1,2; figure 2	4,5
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

Z document member of the same patent family

Date of the actual completion of the international search

30 October 1997

Date of mailing of the international search report

19.11.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 eponl,
Fax: (+31-70) 340-3016

Authorized officer

Beugeling, G.L.H.

INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/CA 97/00522

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	DE 195 32 685 A (ROTHER) 6 March 1997 see the whole document ---	2-5,7,8, 10,17, 18,23,25
X	DE 42 28 597 A (BITTNER) 3 March 1994 see the whole document -----	17,18,22

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CA 97/00522

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4649069 A	10-03-87	AU 586819 B AU 4227785 A EP 0161637 A US 4766022 A	27-07-89 14-11-85 21-11-85 23-08-88
GB 1546901 A	31-05-79	AU 1886376 A DE 2647113 A FR 2328432 A JP 52056725 A	27-04-78 05-05-77 20-05-77 10-05-77
US 5382462 A	17-01-95	NONE	
US 5191692 A	09-03-93	NONE	
DE 19532685 A	06-03-97	NONE	
DE 4228597 A	03-03-94	NONE	

Form PCT/ISA/210 (patent family annex) (July 1992)